Matching Guide for Loaders

Medium and Large Wheel Loaders

Maker	Tire Size Model	15.5R25	17.5R25	20.5R25	550/65R255	600/65R25	650/65R25	23.5R25	26.5R25	750/65R25	775/65R29	29.5R25	875/65R29	29.5R29	35/65R33	45/65R39	45/65R45	50/65R51	55.5/80R57	60/80R57
	910	0																		
	914		0																	
	924		0	0	0															
	930			0	0		0													
	938			0	0		0													
	950							0		0										
	962							0		0										
	966								0	0	0									
Caterpillar	972								0	0	0									
	980											0	0							
	982												0	0						
	986														0					
	988														0					
	990															0				
	992																0			
	993																	0		
	994																			0
	WA120	0	0																	
	WA180	0	0																	
	WA250		0	0																
	WA320		0	0																
	WA380							0												
	WA400							0												
Komatsu	WA420							0	0											
	WA450								0											
	WA480								0											
	WA500								0			0								
	WA600														0					
	WA800																0			
	WA900																0			
	WA1200																		0	
	L40	0																		
	L45	0																		
	L50		0																	
	L60		0	0		0														
	L70			0		0														
	L90			0		0	0													
Volvo	L110							0		0										
	L120 L150							U	0	0	0									
	L180 L220								0		0									
	L220 L250											0	0							
	L250											0	0							
	L350														0					

Small and Compact Loaders

Maker	Tire Size Model	335/80R20	365/80R20	405/70R2
Caterpillar	908			0
	WA75	0		
Komatsu	WA85		0	
	WA90			0



For all your loader and dozer radial tire needs BRIDGESTONE PROVIDES THE BEST SOLUTIONS

Our comprehensive range of industry-leading loader/dozer tires featuring proven patterns and construction deliver superior performance in all operating conditions — from soft and muddy to extremely hard rock conditions. Bridgestone will provide reduced operating cost, and higher productivity with extreme durability.



4		VSW	VUT	VLT	VJT	VTS	VLTS	VSNT	VSDT	VSDL	VSDR	VSMS	VSMS2
	Pattern	V-Steel Snow Wedge L-2	V-Steel Ultra Traction L-2	V-Steel L-Traction L-3	V-Steel J-Traction L-3	V-Steel Traction-Stability L-3	V-Steel L-Traction S L-4	V-Steel N-Traction L-4	V-Steel Super Deep Traction L-5	V-Steel D-Lug L-5	V-Steel Super Deep Rock L-5	V-Steel Smooth Tread-MS L-5S	V-Steel Smooth Tread-MS2 L-5S
	Feature	Excellent traction, cornering and braking performance on ice and snow.	Superior traction, self-cleaning, maneuverability and performance.		Low vibration, superior riding comfort, long life and high traction.	Low-profile design and an excellent combination of traction and stability.	Excellent traction and long life on rocky and gravel surfaces.	With deep treads ideally designed for tough loader/dozer operations.	Extra-deep, wide tread pattern assures superior cut resistance and long tread life.	Extra-deep tread for a good balance of cut resistance, traction and long tread life.	Improved wear-and-tear resistance compared to VSDL.	Smooth extra-deep tread design maximizes cut resistance.	Optimized sidewall shape to maximize side cut resistance and increase tire life compared to VSMS.
	Tread depth	Standard	Standard	Standard	Standard	Standard	Deep	Deep	Extra-Deep	Extra-Deep	Extra-Deep	Extra-Deep	Extra-Deep
(Characteristic	Snow operation	Economical radial	Flotation on muddy surface	High total performance	High total performance	Traction	Traction	Traction	Rock	Rock	Smooth	Smooth
	ecommended round surface												
	8.25R15									•			
	10.00R15									•			
	14.5R15									•			
	9.00R20											•	
	12.00R20									•		•	
	14.00R20									● VSNL*1			
	12.00R24											•	
es	14.00R24	●* ²										•	
serie	15.5R25		•							•			
	17.5R25	•	•		•					•		•	
8	18.00R25											•	
	20.5R25	•	•	•	•		•			•	•		
	23.5R25	•	•	•	•		•		•	•			
	26.5R25			•	•			•	•	•		•	•
	29.5R25			•	•			•	•	•			
	29.5R29							•	•	•		•	•
	55.5/80R57									•			
	60/80R57									•			
	550/65R25					•							
	600/65R25	•											
	650/65R25					•							
Ø	750/65R25			•									
ries	775/65R29					•							
5 seri	875/65R29					•	•						
99	35/65R33							•	•	● VSNL*1			
	45/65R39									•			
	45/65R45									● VSNL*1			
	50/65R51									•			

^{*1} TRA code is L-4. *2 for Semi-Drop Center Rim.

Availab